

AGCO, Your Agriculture Company, is a premier manufacturer of agricultural equipment, providing high-tech solutions for professional farmers feeding the world. The company is dedicated to delivering superior customer service, innovation and quality. AGCO products are distributed in more than 140 countries worldwide.

AGCO FINANCE

At AGCO Finance, we understand that financing is as much a part of your purchase decision as the features and benefits of the product. So we're committed to providing the best means of acquiring the equipment you need, while allowing you to preserve other credit lines of operating capital.

See your authorized TerraGator dealer for:

- Competitive Rates
- Comprehensive Financing
- Flexible Payment Schedules
- Flexible Terms
- Quality Service
- Leasing Options
- Virtually Unlimited Resources

AGCO ANSWERS

At AGCO, customer care isn't just a department. It's a commitment. Contact us with your questions, we'll do our best to answer them promptly or put you in touch with someone who can.

877-525-4384 or agcoanswers@agcocorp.com

SprayParts.com

When you purchase a TerraGator, you get the backing and support of our world-class dealers who take productivity to heart. Combine that with our 24-hour-a-day parts network, and you have the absolute gold standard in dealer support. *SprayParts.com* is your 24/7/365 resource for a complete line of quality replacement parts and accessories.



See more at applylikeapro.com

SPECIFICATIONS

NUTRIENT MANAGEMENT SYSTEM | MODELS 3244 • 9205



TerraGator NUTRIENT MANAGEMENT SYSTEM | 3244 • 9205 | SPECIFICATIONS



TerraGator® is a worldwide brand of AGCO Corporation.

© 2009 AGCO Corporation. AGCO® and TerraGator® are registered trademarks of AGCO Corporation. CAT® is a registered trademark of Caterpillar, Inc. AGCO Corporation has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. AGCO Corporation is not responsible for differences between the specifications or illustrations contained in this publication and the actual equipment. Equipment produced by other manufacturers is shown in photographs in this brochure for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. All rights reserved. AGCO Corporation, 4205 River Green Parkway, Duluth, GA 30096. NMS09381 (09) 15 ADV O&B 37923-01 DS



SPECIFICATIONS COMMON TO BOTH MODELS

APPLICATION CAB	
Seat	Sears VRS (Vibration reduction system) seat
Suspension	Air cab suspension
Air Conditioning	Full electronic cab control
Filtering	Three stage air filtering, meets ASAE 525 standards
TIRES	
Front/Rear	Michelin 1050/50 R32 Standard
ELECTRICAL SYSTEM	
Alternator	200 Amp
Batteries	3 x 12 Volt Cold Cranking Amps
Control with CANBUS	System, Engine, Transmission & Lights



9205

ENGINE	
Type	CAT C-13 12.5 ltr. (763 cu. in.) Tier III / Stage 3A
Horsepower	425 HP (317 kW)
Max Power	459 HP (369 kW)
Max Torque	1400 RPM (1510 ft.-lbs.)
Fuel Capacity	200 Gallons (757 L)
TRANSMISSION	
Powershift	Caterpillar TA22, 16F/3R
Transport Speed	Vehicle speed to comply with speed limitations for the tires
Drive	4-wheel drive
Differential	Lockable interaxle differential for maximum traction
AXLES	
Type	Axle Tech with outboard planetary reduction
DIMENSIONS	
Overall Width	11' (3.4 m)
Length without (Chassis)	33.8' (10.3 m)
Wheelbase	26.6' (8.1 m)
Height (Chassis)	12.3' (3.7 m)
NMS LIQUID SYSTEM	
Control	Falcon VT Terminal & NMS Joystick
Pump	Borger 1585 / 2380 Gallons per minute (150 L/sec)
Tank Capacity	5283 Gallons
Loading Arm	10" (25.4 cm) reload arm with Hyd functions from cab
Superload System	3,302 Gal/per minute (208.3 L/sec) [depending on viscosity]
Hitch	Category III, Stabilization chain w/spring, Hitch lift adjustment
NMS DRY SYSTEM	
Control	Falcon VT & NMS Joystick
Capacity	20 Cu Yd (15.2 cu. m)
Application Rates	1 Ton/ Ac up to 40 Tons/ Ac (depending on Density)
Spreading Width	60' (18.3 m) [Depending on density]
Bottom Chain	12.5 cm Rubigs Chain
Dosing Gate	Hydraulic variable dosing gate
Adjustable Disc gate	Adjustments from 3/4" - 2 3/4" (1.9 - 6.9 cm) to fine tune spread pattern
Spreading Discs	Two - 4' (1.2 m) diameter spreading discs with 8 vanes
Beater	One or two beater
PTO	Hydraulic driven PTO

3244

ENGINE	
Type	CAT C-11 11.1 ltr. (677 cu.in.) Acert Tier III / Stage 3A
Horsepower	364 HP (271 kW)
Max Power	395 HP (295 kW)
Max Torque	1400 RPM (1292 ft.-lbs.)
Fuel Capacity	198 Gallons (750 L)
TRANSMISSION	
Powershift	Caterpillar 16F/3R
Transport Speed	Vehicle speed to comply with speed limitations for the tires
Drive	4-wheel drive, with switch enable to operate 2-wheel drive
Differential	—
AXLES	
Type	Axle Tech Type PRC 2715
DIMENSIONS	
Overall Width	10.3' (3.1 m)
Length without (Chassis)	29.8' (9.1 m)
Wheelbase	20.1' (6.1 m)
Height (Chassis)	12.7' (3.9 m)
NMS LIQUID SYSTEM	
Control	Falcon VT Terminal & NMS Joystick
Pump	Borger 1585 / 2380 Gallons per minute (150 L/sec)
Tank Capacity	4755 Gallons
Loading Arm	10" (25.4 cm) reload arm with Hyd functions from cab
Superload System	3,302 Gal/per minute (208.3 L/sec) [depending on viscosity]
Hitch	Category III, Stabilization chain w/spring, Hitch lift adjustment
NMS DRY SYSTEM	
Control	Falcon VT & NMS Joystick
Capacity	18.5 Cu Yd (15.2 cu. m)
Application Rates	1 Ton/ Ac up to 40 Tons/ Ac (depending on Density)
Spreading Width	60' (18.3 m) [Depending on density]
Bottom Chain	12.5 cm Rubigs Chain
Dosing Gate	Hydraulic variable dosing gate
Adjustable Disc gate	Adjustments from 3/4" - 2 3/4" (1.9 - 6.9 cm) to fine tune spread pattern
Spreading Discs	Two - 4' (1.2 m) diameter spreading discs with 8 vanes
Beater	One or two beater
PTO	Hydraulic driven PTO

