

AGCO, Your Agriculture Company, is a premier manufacturer of agricultural equipment, providing high-tech solutions for professional farmers feeding the world. The company is dedicated to delivering superior customer service, innovation and quality. AGCO products are distributed in more than 140 countries worldwide.

AGCO FINANCE

At AGCO Finance, we understand that financing is as much a part of your purchase decision as the features and benefits of the product. So we're committed to providing the best means of acquiring the equipment you need, while allowing you to preserve other credit lines of operating capital.

See your authorized SpraCoupe dealer for:

- Competitive Rates
- Comprehensive Financing
- Flexible Payment Schedules
- Flexible Terms
- Quality Service
- Leasing Options
- Virtually Unlimited Resources

AGCO ANSWERS

At AGCO, customer care isn't just a department. It's a commitment. Contact us with your questions, we'll do our best to answer them promptly or put you in touch with someone who can.

877-525-4384 or agcoanswers@agcocorp.com

SprayParts.com

When you purchase a SpraCoupe, you get the backing and support of our world-class dealers who take productivity to heart. Combine that with our 24-hour-a-day parts network, and you have the absolute gold standard in dealer support. *SprayParts.com* is your 24/7/365 resource for a complete line of quality replacement parts and accessories.



See more at applylikeapro.com

SPECIFICATIONS

SPRACOUPE® SPRAYERS FOR PRE- & POST-EMERGENCE APPLICATIONS | 4000 • 7000



SpraCoupe 4000 • 7000 | SPECIFICATIONS



SpraCoupe® is a worldwide brand of AGCO Corporation.

© 2009 AGCO Corporation. AGCO® and SpraCoupe® are registered trademarks of AGCO Corporation. CAT® is a registered trademark of Caterpillar, Inc. AGCO Corporation has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. AGCO Corporation is not responsible for differences between the specifications or illustrations contained in this publication and the actual equipment. Equipment produced by other manufacturers is shown in photographs in this brochure for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. All rights reserved. AGCO Corporation, 4205 River Green Parkway, Duluth, GA 30096. SC09382 (09) 15 ADV O&B 37923-01 DS



4000 SERIES

SPECIFICATIONS

OPTIONS:

- Belly Shields: Easy to attach and remove, belly shields protect your investment in both your crop and your machine.
- Tow Bar: Attach the optional telescoping tow bar and tow the applicator to the field.
- Crop Deflectors: Move foliage out of the tire tracks and reduce potential crop damage.
- Floodlight Kit: Light up the field for low light and nighttime operations.
- Foam Marker: Mark your field position clearly for spray swath accuracy.
- Front Axle & Drive Shaft Extension: Six-inch extensions allow 80-108 in. (203-274 cm) machines to be extended to 92-120 in. (234-304 cm).

	4460	4660
Empty Weight – lb. (kg)	9,856 (4,471)	9,979 (4,526)
Operating Weight – lb. (kg)	13,700 (6,214)	13,823 (6,270)
Clearance – in. (cm)	Automatic: 36 (91.5) Manual 38 (96.5)	Automatic: 46 (116.8) Manual 48 (121.9)
ENGINE		
Make – HP	Perkins® 125	
Type	1104D 4.4L / Certified EPA Non-Road Tier III	
Low Idle Speed – rpm	850	
Governed (full load) – rpm	2,200	
Fuel	Diesel	
Fuel Capacity – gal. (L)	44 (166.6)	
Engine Oil Capacity – qts. (L)	9 (8.5)	
TRANSMISSION		
Type	BorgWarner T-5, 5-speed manual or Allison 2100 RDS 5-speed automatic	
Transmission Oil Capacity – qts. (L)	BorgWarner 2.8 (2.65) or Allison 15 (14)	
SPEED RANGES		
	Automatic Manual	
1st – mph (kph)	4.2 (6.8) 3.9 (6.3)	
2nd – mph (kph)	7.2 (11.6) 6.8 (10.9)	
3rd – mph (kph)	9.2 (14.8) 10.2 (16.4)	
4th – mph (kph)	13.0 (21.9) 13.6 (21.9)	
5th – mph (kph)	18.3 (29.5) 18.9 (30.4)	
Reverse – mph (kph)	2.9 (4.7) 4.3 (6.9)	
TIRES/SUSPENSION/TRACK WIDTH		
Front	10-16 (Single Front only) 9-24 8 ply, 320/85 R25	9-24 8 ply, 320/85 R25
Rear (Standard)	320/85R24 12 ply, 380/85 R24, 230/95 R32	320/85R24 12 ply, 380/85 R24, 230/95 R32
Front Suspension	Independent strut and spring suspension with oscillating front axle	
Rear Suspension	Independent knee action suspension with coil spring	
Track Width – in. (cm)	72 or 80 – 108 (182.8 or 203.2 – 259.1)	80 – 108 (203.2 – 259.1)
SPRAYING SYSTEM		
Spray Control	Raven™ 460	
Product Pump	Engine-mounted, belt-driven Hypro® centrifugal pump with electromagnetic clutch	
Agitation	Manual adjust with electric on/off switch in cab	
Liquid Tank Capacity – gal. (L)	400 (1,514)	
Filtration	50 mesh	
BOOM		
Spraying Width – ft. (m)	60 (18.3) or 80 (24.4) or 60/80 (18.3/24.4)	
Sections	3 on 60', 5 on 80' and 60/80'	
BOOM HEIGHT		
Low Position – in. (cm)	9 – 64 (229 – 1,626)	21 – 76 (533 – 1,930)
High Position – in. (cm)	25 – 80 (635 – 2,032)	37 – 92 (940 – 2,337)

	7460	7660
Empty weight – lb. (kg)	17,500 (7,938)	18,000 (8,165)
Operating weight – lb. (kg)	23,500 (10,659)	24,000 (10,866)
Clearance – in. (cm)	42 (106.7)	48 (121.9)
ENGINE		
Make/HP	Perkins®/174	
Type	1106D, 6.0L / Certified EPA Non-Road Tier III	
Low Idle Speed	850	
Governed (full load)	2500	
Fuel	Diesel	
Fuel Capacity – gal. (L)	65.0 (246.1)	
Engine Oil Capacity – qts. (L)	14.0 (13.2)	
TRANSMISSION		
Type	Caterpillar PG 115 PowerShift, 6 forward and 2 reverse speeds	
Transmission Oil Capacity – gal. (L)	8.0 (30.3)	
SPEED RANGES		
1st – mph (k/h)	6.4 (10.3)	
2nd – mph (k/h)	10.0 (16.1)	
3rd – mph (k/h)	13.2 (21.2)	
4th – mph (k/h)	18.3 (29.5)	
5th – mph (k/h)	20.8 (33.5)	
6th – mph (k/h)	27.5 (44.3)	
Reverse 1 – mph (k/h)	6.4 (10.3)	
Reverse 2 – mph (k/h)	13.5 (21.7)	
TIRES/SUSPENSION/TRACK WIDTH		
Front	12.4 x 28	320/85R38 (optional 540/65R24 or 380/80R38)
Rear	380/80 R46 standard (optional 320/90R46, 480/80R46, or 620/70R42)	
Front Suspension	Independent strut with linear rate suspension springs and hydraulic track width adjustment	
Rear Suspension	Independent “knee action” suspension incorporated into chain case design with hydraulic suspension and hydraulic track width adjustment	
Track width – in. (cm)	71 – 89 (180.3 – 226.1)	88 – 120 (223.5-304.8) optional 120 – 152 (304.8 – 386.1)
SPRAYING SYSTEM		
Spray Control	Raven™ 5000 standard, optional Raven™ Viper Pro and Falcon VT	
Flow Control	PWM hydraulic or product servo valve	
Agitation	Manual adjust with electric on/off switch in cab	
Liquid Tank Capacity – gal. (L)	724 (2,744) Poly or 660 (2,498) Stainless Steel	
Rinse Tank Capacity – gal. (L)	65 (246)	
Product Pump	Hypro® 9303	
Filtration	50 mesh	
BOOMS		
Spraying Width – ft. (m)	60/80 (18.3/24.4) – optional 60/90 (18.3/27.4)	
Sections	5	
Nozzle Spacing – in. (cm)	20 (50.8)	
BOOM HEIGHT – HYDRAULIC ADJUSTMENT		
Low Position – in. (cm)	17 – 74 (43.2 – 188)	23 – 80 (58.4 – 203.2)
High Position – in. (cm)	33 – 90 (83.8 – 228.6)	39 – 96 (99.1 – 243.8)

7000 SERIES

SPECIFICATIONS

OPTIONS:

- Belly Shields: Easy to attach and remove, belly shields protect your investment in both your crop and your machine.
- Crop Deflectors: Move foliage out of the tire tracks and reduce potential crop damage.
- Work Lights: Light up the field for low light and nighttime operations.
- Foam Marker: Mark your field position clearly for spray swath accuracy.
- Tires: Choose from a variety of combinations that provide greater flotation and minimal soil compaction, while extending the spraying window in wet conditions.

